

ChemFlex 35 Cut

Art.-No.: 907000 | Cat: III

Description:

Cut-resistant chemical protection glove type A made of 18 gauge nylon fine knit and HPPE fibre, triple nitrile dipped with sandy finish on palm and fingertips, suitable for use with food, contact heat protection, cut protection level D, AQL 1.5, layer thickness: 1.2 mm, length: 35 cm

Base material: 18 gauge nylon, HPPE fibre

Coating: nitrile, nitrile foam

Sizes: 8 - 12

Colour: green

Packing unit: 100 / 10 pairs



EN 388



4X42D

EN 407



X1XXXX



☒	☐	☐	☐	☐	Breathability
☒	☒	☒	☒	☒	Water protection
☒	☒	☒	☒	☐	Cut protection
☒	☒	☒	☒	☐	Sensitivity
☒	☒	☒	☒	☐	Dry grip
☒	☒	☒	☒	☐	Wet/oil grip

EN 374-1



Typ A

EN 374-5



Tested chemicals

J - n-Heptane
K - Sodium hydroxide 40 %
L - Sulphuric acid 96 %
O - Ammonium hydroxide 25 %
P - Hydrogen peroxide 30 %
T - Formaldehyde 37 %

0075

Applied EN standards:

EN ISO 21420:2020, EN 388:2016+A1:2018, EN 407:2020, EN ISO 374-1:2016+A1:2018

EN Guide



Declaration of conformity

We hereby declare that the Personal Protective Equipment (PPE) described above complies with the provisions of Regulation (EU) 2016/425 and is identical to the PPE which was the subject of the EC Type Examination Certificate issued by the following accrediting testing institute:

CTC (NB 0075)
4, rue Hermann Frenkel
69367 Lyon cedex 07 - France

Cert. No: 0075/1277/162/02/25/0276

Jever, 22.05.2023

Place, date

Hase
Safety Gloves GmbH
Am Hillernsen Hamm 6
26441 Jever
Tel.: 0 44 61 / 9 22 20 · Fax: 0 44 61 / 92 22 99
email: gloves@hase-safety.com
Internet: www.hasesafetygloves.com

Klaus Burgdorff, managing director

Company, signature

